NSN 5305-00-934-0538

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-934-0538 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.182 inches and 0.275 inches **Fastener Length:** Between 0.344 inches and 0.375 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.307 inches and 0.312 inches **Internal Drive Style:** Slot **Thread Diameter:** 0.164 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 60000 pounds per square inch **Countersink Angle:** Between 80.0 degrees and 82.0 degrees **Screw Material:** Steel **Screw Material Specification:** Qq-s-634 federal specification single material response or qq-s-637 federal specification single material response or 66 federal standard single material response **Screw Surface Treatment:** Cadmium and chromate **Screw Surface Treatment Specification:** Qq-p-416, type 2, cl 3 federal specification all treatment responses **Thread Series Designator:** Unc **Specification Or Standard:** 1 type and s style **Departure From Cited Designator:** As modified by head diameter Shelf Life: N/a **Unit Of Measure:**

No

Demilitarization:

NSN 5305-00-934-0538 Machine Screw - Page 2 of 2



Fiig:

A500d0