NSN 5305-00-934-8834

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-934-8834 **Thread Direction:** Right-hand Thread Length: 0.320 inches Fastener Length: 1.440 inches **Head Style:** Knurled no. 4 **Head Diameter:** 0.500 inches **Head Height:** 0.560 inches First Diameter From Head: 0.380 inches **Second Diameter From Head:** Between 0.176 inches and 0.182 inches **Third Diameter From Head:** 0.250 inches **Fourth Diameter From Head:** Between 0.176 inches and 0.182 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.860 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: 1.500 inches Distance From Largest Bearing Surface Of Head To End Of Third Diameter: 1.820 inches **Internal Drive Style:** Slot **Thread Diameter:** 0.250 inches Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity:** 3 Material: Steel comp 303 **Surface Treatment: Passivate Thread Series Designator:**

Unc Shelf Life: N/a

NSN 5305-00-934-8834

Externally Relieved Body Screw - Page 2 of 2



	1	:.	~	84				
ι	JN	IT	UΤ	IVI	ea	Sι	ire:	•

--

Demilitarization:

No

Fiig:

A003b0