NSN 5305-00-935-2985

Shoulder Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-935-2985 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.418 inches and 0.438 inches **Fastener Length:** Between 2.418 inches and 2.438 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.419 inches and 0.437 inches **Head Height:** Between 0.209 inches and 0.219 inches **Shoulder Diameter:** 0.3080 inches first shoulder and 0.3100 inches first shoulder **Shoulder Length:** 2.000 inches first shoulder **Internal Drive Style:** Hexagon **Thread Diameter:** 0.250 inches Width Across Flats: 0.156 inches Thready Qty Per Inch (tpi): 20 Min. Tensile Strength (psi): 140000 pounds per square inch **Hardness Rating:** 32.0 rockwell c and 43.0 rockwell c **Shoulder Shape:** Round first shoulder Material: Steel **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Qq-p-416, ty2 cl3 federal specification single treatment response **Thread Series Designator:** Unc

Shelf Life:

N/a

NSN 5305-00-935-2985

Shoulder Screw - Page 2 of 2



	1	:.	~	84				
ι	JN	IT	UΤ	IVI	ea	Sι	ire:	•

--

Demilitarization:

No

Fiig:

A003b0