NSN 5305-00-936-2964

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-936-2964 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.203 inches and 0.234 inches **Fastener Length:** Between 0.234 inches and 0.266 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.134 inches and 0.140 inches **Head Height:** Between 0.083 inches and 0.086 inches **Internal Drive Style:** Hexagon **Thread Diameter:** 0.086 inches Width Across Flats: Between 0.078 inches and 0.079 inches Thready Qty Per Inch (tpi): 64 Min. Tensile Strength (psi): 80000 pounds per square inch Hardness Rating: 80.0 rockwell b Minimum Yield Strength: 30000 pounds per square inch Material: Steel comp 3130 **Material Specification:** Mil-s-16974 military specification single material response **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response

Thread Series Designator:

Unf

Specification Data:

80205-nas1351 professional/industrial association standard

Shelf Life:

N/a

NSN 5305-00-936-2964

Socket Head Cap Screw - Page 2 of 2



Unit Of Mea	sure:
-------------	-------

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-16974 spec.