NSN 5305-00-936-4022

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-936-4022 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.218 inches **Fastener Length:** Between 0.594 inches and 0.625 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.270 inches and 0.332 inches First Diameter From Head: Between 0.120 inches and 0.125 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.376 inches and 0.407 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.164 inches Thready Qty Per Inch (tpi): 32 **Countersink Angle:** Between 99.0 degrees and 101.0 degrees **Externally Relieved Body Diameter Quantity:** 1 **Special Features:** Nylon pellet in thd Material: Iron alloy 660 **Material Specification:** Ams 5735 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Mil-f-14072, finish e300 military specification single treatment response **Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure:**

--

NSN 5305-00-936-4022

Externally Relieved Body Screw - Page 2 of 2



_										
וו	0	m	ш	м	2	iza	31	^	n	

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-f-14072 spec.