NSN 5305-00-936-4036

Shoulder Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-936-4036 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.161 inches and 0.181 inches **Fastener Length:** Between 0.285 inches and 0.305 inches **Head Style:** Flat chamfer **Head Diameter:** 0.343 inches **Head Height:** 0.090 inches **Shoulder Diameter:** 0.151 inches first shoulder and 0.156 inches first shoulder **Shoulder Length:** 0.114 inches first shoulder **Internal Drive Style:** Slot **Thread Diameter:** 0.112 inches Thready Qty Per Inch (tpi): 40 **Shoulder Shape:** Round first shoulder Material: Steel comp 303 **Material Specification:** Qq-s-764, cond a federal specification single material response **Surface Treatment: Passivate Surface Treatment Specification:** Mil-f-14072, e300 military specification single treatment response **Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure:**

Demilitarization: No

NSN 5305-00-936-4036

Shoulder Screw - Page 2 of 2



Fiig:

A003b0

Mil-std (military Standard):

Mil-f-14072 spec.