

View Online at <https://aerobasegroup.com/nsn/5305-00-936-5995>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.260 inches

Fastener Length:

0.393 inches

Head Style:

Hexagon

Head Height:

Between 0.140 inches and 0.172 inches

Width Between Flats:

Between 0.428 inches and 0.440 inches

Hole Diameter:

0.046 inches

Point Length:

0.133 inches

Point Diameter:

Between 0.187 inches and 0.190 inches

Point Style:

Flat

Internal Drive Style:

W/o internal drive

Thread Diameter:

0.250 inches

Hole Quantity:

3

Hole Type:

Drilled

Thready Qty Per Inch (tpi):

28

Hole Configuration Style:

Hexagon flats

Point Chamfer Angle:

45.0 degrees

Material:

Steel comp 4130 or steel comp 8630 or steel comp 8735 or steel comp 8740 or steel comp 4140

Material Specification:

Mil-s-6049 military specification 1st material response or mil-s-6050 military specification 2nd material response or mil-s-6098 military specification 3rd material response or mil-s-6758 military specification 4th material response or an-s-9 military specification 5th material response or mil-s-5626 military specification 6th material response

Surface Treatment:

Cadmium and chromate or cadmium and phosphate

Surface Treatment Specification:

Qq-p-416 type 2 class 2 federal specification 1st treatment response and qq-p-416 type 2 class 2 federal specification 2nd treatment response or qq-p-416 type 3 class 2 federal specification 3rd treatment response and qq-p-416 type 3 class 2 federal specification 4th treatment response

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-6049 spec.