

View Online at <https://aerobasegroup.com/nsn/5305-00-936-5995>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

0.260 inches

**Fastener Length:**

0.393 inches

**Head Style:**

Hexagon

**Head Height:**

Between 0.140 inches and 0.172 inches

**Width Between Flats:**

Between 0.428 inches and 0.440 inches

**Hole Diameter:**

0.046 inches

**Point Length:**

0.133 inches

**Point Diameter:**

Between 0.187 inches and 0.190 inches

**Point Style:**

Flat

**Internal Drive Style:**

W/o internal drive

**Thread Diameter:**

0.250 inches

**Hole Quantity:**

3

**Hole Type:**

Drilled

**Thready Qty Per Inch (tpi):**

28

**Hole Configuration Style:**

Hexagon flats

**Point Chamfer Angle:**

45.0 degrees

**Material:**

Steel comp 4130 or steel comp 8630 or steel comp 8735 or steel comp 8740 or steel comp 4140

**Material Specification:**

Mil-s-6049 military specification 1st material response or mil-s-6050 military specification 2nd material response or mil-s-6098 military specification 3rd material response or mil-s-6758 military specification 4th material response or an-s-9 military specification 5th material response or mil-s-5626 military specification 6th material response

**Surface Treatment:**

Cadmium and chromate or cadmium and phosphate

**Surface Treatment Specification:**

Qq-p-416 type 2 class 2 federal specification 1st treatment response and qq-p-416 type 2 class 2 federal specification 2nd treatment response or qq-p-416 type 3 class 2 federal specification 3rd treatment response and qq-p-416 type 3 class 2 federal specification 4th treatment response

**Thread Series Designator:**

Unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0

**Mil-std (military Standard):**

Mil-s-6049 spec.