NSN 5305-00-936-9622



Machine Screw - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5305-00-936-9622 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 1.214 inches and 1.251 inches **Fastener Length:** Between 1.204 inches and 1.251 inches **Head Style:** Pan no. 2 **Head Diameter:** Between 0.473 inches and 0.492 inches **Head Height:** Between 0.162 inches and 0.175 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.250 inches Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 125000 pounds per square inch **Hardness Rating:** Between 26.0 rockwell c and 32.0 rockwell c **Screw Material:** Steel comp 4037 or steel comp 8630 **Screw Material Specification:** Ams 6300 assn standard 1st material response or mil-s-6050 military specification 2nd material response **Screw Surface Treatment:** Cadmium and chromate **Screw Surface Treatment Specification:** Qq-p-416, type 2, class 3 federal specification single treatment response **Thread Series Designator:** Unf Shelf Life: N/a **Unit Of Measure:**

No Fiig:

· ···g·

A500d0

Demilitarization:

NSN 5305-00-936-9622

Machine Screw - Page 2 of 2



Mil-std (military Standard):

Mil-s-6050 spec.