NSN 5305-00-937-1779

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-937-1779

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
0.276 inches
Fastener Length:
0.838 inches
Head Style:
Flat countersunk
Head Diameter:
Between 0.297 inches and 0.302 inches
Internal Drive Style:
High-torque
Thread Diameter:
0.190 inches
Thready Qty Per Inch (tpi):
32
Min. Tensile Strength (psi):
180000 pounds per square inch
Hardness Rating:
Between 40.0 rockwell c and 43.0 rockwell c
Countersink Angle:
100.0 degrees
Screw Material:
Steel comp 8630 or steel comp 4037
Screw Material Specification:
Mil-s-6050 military specification 1st material response or ams 6300 assn standard 2nd material response
Screw Surface Treatment:
Cadmium and chromate
Screw Surface Treatment Specification:
Qq-p-416, type 2, class 3 federal specification single treatment response
Thread Series Designator:
Unf
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A500d0

NSN 5305-00-937-1779

Machine Screw - Page 2 of 2



Mil-std (military Standard):

Mil-s-6050 spec.