NSN 5305-00-937-6506

Setscrew - Page 1 of 2

Thread Class:

Thread Direction:

За



View Online at https://aerobasegroup.com/nsn/5305-00-937-6506

| Right-hand |
|--|
| Thread Length: |
| Between 0.218 inches and 0.289 inches |
| Fastener Length: |
| Between 0.284 inches and 0.289 inches |
| Head Style: |
| Flat chamfer |
| Head Diameter: |
| Between 0.365 inches and 0.375 inches |
| Head Height: |
| Between 0.244 inches and 0.250 inches |
| Point Length: |
| 0.063 inches |
| Point Style: |
| Flat |
| Internal Drive Style: |
| Hexagon |
| Thread Diameter: |
| 0.250 inches |
| Width Across Flats: |
| Between 0.187 inches and 0.190 inches |
| Thready Qty Per Inch (tpi): |
| 28 |
| Min. Tensile Strength (psi): |
| 80000 pounds per square inch |
| Hardness Rating: |
| 80.0 rockwell b |
| Minimum Yield Strength: |
| 30000 pounds per square inch |
| Point Chamfer Angle: |
| 90.0 degrees |
| Special Features: |
| Hole drilled through longitudinal axis 0.070 in. Dia |
| Material: |
| Steel comp 302 or steel comp 303 or steel comp 304 or steel comp 305 or steel comp 316 |
| Material Specification: |
| 66 federal standard all material responses |
| Surface Treatment: |
| Passivate |
| |

NSN 5305-00-937-6506

Setscrew - Page 2 of 2



| Surface Treatment Speci |
|-------------------------|
|-------------------------|

171, finish no. 5.4.1 military standard single treatment response

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0