NSN 5305-00-939-0657



Shoulder Screw - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5305-00-939-0657 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.355 inches and 0.375 inches **Fastener Length:** Between 1.860 inches and 1.870 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.357 inches and 0.375 inches **Head Height:** Between 0.177 inches and 0.187 inches **Shoulder Diameter:** 0.246 inches first shoulder and 0.248 inches first shoulder **Shoulder Length:** 1.495 inches first shoulder and 1.505 inches first shoulder **Internal Drive Style:** Hexagon **Thread Diameter:** 0.190 inches Width Across Flats: 0.125 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 140000 pounds per square inch **Hardness Rating:** 32.0 rockwell c and 43.0 rockwell c **Shoulder Shape:** Round first shoulder Material:

Steel comp 4037 or steel comp 4137 or steel comp 4140 or steel comp 8630 or steel comp 8740

Surface Treatment:

Cadmium and chromate

Surface Treatment Specification:

Qq-p-416 type 2 cl 3 federal specification single treatment response

Thread Series Designator:

Unc

Shelf Life:

N/a

NSN 5305-00-939-0657

Shoulder Screw - Page 2 of 2



ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

No

Fiig:

A003b0