NSN 5305-00-939-0866

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-939-0866

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
0.276 inches
Fastener Length:
Between 0.573 inches and 0.603 inches
Head Style:
Pan
Head Diameter:
Between 0.331 inches and 0.373 inches
Head Height:
Between 0.122 inches and 0.133 inches
Grip Diameter:
Between 0.1885 inches and 0.1895 inches
Internal Drive Style:
Offset cruciform (torque set)
Thread Diameter:
0.190 inches
Grip Length:
0.312 inches
Thready Qty Per Inch (tpi):
32
Min. Tensile Strength (psi):
140000 pounds per square inch
Hardness Rating:
248.0 brinell standard and 321.0 brinell standard
Surface Finish:
32.0 microinches threads
Material:
Iron alloy 660
Material Specification:
Ams 5732 assn standard single material response
Surface Treatment:
Passivate
Surface Treatment Specification:
Qq-p-35 federal specification single treatment response
Thread Series Designator:
Unjf
Specification Data:
80205-nas1133 professional/industrial association standard

NSN 5305-00-939-0866

Close Tolerance Screw - Page 2 of 2



_			•		
•	n	ο.	•	18	e:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0