# NSN 5305-00-939-9208

Machine Screw - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5305-00-939-9208



#### Thread Class:

2a

**Thread Direction:** 

**Right-hand** 

# Thread Length:

Between 0.688 inches and 0.750 inches

#### Fastener Length:

0.750 inches

Head Style:

Fillister

#### Head Diameter:

Between 0.250 inches and 0.270 inches

#### **Head Height:**

Between 0.106 inches and 0.113 inches

#### Hole Diameter:

# 0.046 inches

Internal Drive Style:

Slot

**Thread Diameter:** 

0.164 inches

#### **Hole Quantity:**

1

# Thready Qty Per Inch (tpi):

32

# Min. Tensile Strength (psi):

80000 pounds per square inch

# **Screw Material:**

Steel comp 302 or steel comp 303 or steel comp 304 or steel comp 305 or steel comp 316

# **Screw Material Specification:**

66 federal standard all material responses

# **Screw Surface Treatment:**

Passivate

# Screw Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

# Head Hole Configuration Style:

Round

**Thread Series Designator:** 

Unc

Shelf Life:

N/a

#### Unit Of Measure:

---

# NSN 5305-00-939-9208

Machine Screw - Page 2 of 2

Demilitarization:

No

Fiig:

A500d0

