NSN 5305-00-940-8908

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-940-8908 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.250 inches **Fastener Length:** 4.750 inches **Head Style:** Flat chamfer **Head Diameter:** 0.281 inches **Head Height:** 0.187 inches **First Diameter From Head:** Between 0.157 inches and 0.163 inches **Second Diameter From Head:** Between 0.117 inches and 0.122 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 4.125 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: 4.500 inches **Internal Drive Style:** Slot **Thread Diameter:** 0.164 inches Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity:** 2 **Special Features:** Red enamel color no. 21136 of fed-std-595 Material: Steel comp 303 **Material Specification:** Astm a582 cond a assn standard single material response **Surface Treatment: Passivate**

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

Thread Series Designator:

Unc

NSN 5305-00-940-8908

Externally Relieved Body Screw - Page 2 of 2



Sneit	Lite:
N/a	

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0