## NSN 5305-00-940-9489



Machine Screw - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5305-00-940-9489 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.250 inches and 0.312 inches **Fastener Length:** Between 0.281 inches and 0.312 inches **Head Style:** Fillister **Head Diameter:** Between 0.208 inches and 0.226 inches **Head Height:** Between 0.089 inches and 0.096 inches **Hole Diameter:** 0.046 inches **Internal Drive Style:** Slot **Thread Diameter:** 0.138 inches **Hole Quantity:** Thready Qty Per Inch (tpi): Min. Tensile Strength (psi): 80000 pounds per square inch **Screw Material:** Steel comp 302 or steel comp 303 or steel comp 304 or steel comp 305 or steel comp 316 **Screw Material Specification:** 66 federal standard all material responses **Screw Surface Treatment: Passivate Screw Surface Treatment Specification:** Qq-p-35 federal specification single treatment response

Qq-p-35 federal specification single treatment re
Head Hole Configuration Style:
Round
Thread Series Designator:
Unc
Shelf Life:
N/a
Unit Of Measure:

## NSN 5305-00-940-9489

Machine Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A500d0