

View Online at <https://aerobasegroup.com/nsn/5305-00-940-9516>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 1.250 inches and 1.438 inches

**Fastener Length:**

Between 2.190 inches and 2.250 inches

**Head Style:**

Hexagon

**Head Height:**

Between 0.302 inches and 0.323 inches

**Width Between Flats:**

Between 0.736 inches and 0.750 inches

**Shank Unthreaded Hole Diameter:**

0.107 inches first hole

**Thread Diameter:**

0.500 inches

**Thready Qty Per Inch (tpi):**

20

**Min. Tensile Strength (psi):**

120000 pounds per square inch

**Hardness Rating:**

23.0 rockwell c and 32.0 rockwell c

**Minimum Yield Strength:**

85000 pounds per square inch

**Distance From Head Largest Bearing Surface To Shank Hole Center:**

2.068 inches first hole and 2.088 inches first hole

**Material:**

Steel

**Material Specification:**

Sae gr 5 assn standard single material response

**Surface Treatment:**

Cadmium and chromate

**Surface Treatment Specification:**

Qq-p-416, type 2, cl 3 federal specification single treatment response

**Thread Series Designator:**

Unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A003b0