NSN 5305-00-941-3551

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-941-3551

Thread Class:
2a
Thread Direction:
Right-hand
Thread Length:
Between 0.200 inches and 0.250 inches
Fastener Length:
Between 0.219 inches and 0.250 inches
Head Style:
Fillister
Head Diameter:
Between 0.166 inches and 0.183 inches
Head Height:
Between 0.072 inches and 0.079 inches
Hole Diameter:
0.037 inches
Internal Drive Style:
Slot
Thread Diameter:
0.112 inches
Hole Quantity:
1
Thready Qty Per Inch (tpi):
40
Min. Tensile Strength (psi):
80000 pounds per square inch
Screw Material:
Steel comp 302 or steel comp 303 or steel comp 304 or steel comp 305 or steel comp 316
Screw Material Specification:
66 federal standard all material responses
Screw Surface Treatment:
Passivate
Screw Surface Treatment Specification:
Qq-p-35 federal specification single treatment response
Head Hole Configuration Style:
Round
Thread Series Designator:
Unc
Specification Or Standard:
1 type and 5s style
Shelf Life:
N/a

NSN 5305-00-941-3551

Machine Screw - Page 2 of 2



	1	:.	~	84				
ι	JN	IT	UΤ	IVI	ea	Sι	ire:	•

--

Demilitarization:

No

Fiig:

A500d0