

View Online at <https://aerobasegroup.com/nsn/5305-00-941-3573>

Thread Class:

2a

Thread Direction:

Right-hand

Thread Length:

Between 1.250 inches and 1.437 inches

Fastener Length:

Between 1.938 inches and 2.000 inches

Head Style:

Hexagon

Head Height:

Between 0.302 inches and 0.323 inches

Width Between Flats:

Between 0.736 inches and 0.750 inches

Shank Unthreaded Hole Diameter:

0.107 inches first hole

Thread Diameter:

0.500 inches

Thready Qty Per Inch (tpi):

20

Min. Tensile Strength (psi):

150000 pounds per square inch

Hardness Rating:

32.0 rockwell c and 38.0 rockwell c

Distance From Head Largest Bearing Surface To Shank Hole Center:

1.766 inches first hole and 1.828 inches first hole

Material:

Steel

Surface Treatment:

Phosphate

Surface Treatment Specification:

Mil-p-16232, ty z, cl 2 military specification single treatment response

Thread Series Designator:

Unf

Specification Or Standard:

2 type and 10p style and 8 grade

Departure From Cited Designator:

As mod by thd series

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A003b0

Mil-std (military Standard):

Mil-p-16232 spec.