NSN 5305-00-941-3612

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-941-3612 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.338 inches **Fastener Length:** Between 0.698 inches and 0.728 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.337 inches and 0.387 inches **Grip Diameter:** Between 0.1890 inches and 0.1895 inches **Internal Drive Style:** Offset cruciform (torque set) **Thread Diameter:** 0.190 inches **Grip Length:** 0.379 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: 36.0 rockwell c and 40.0 rockwell c **Countersink Angle:** Between 99.0 degrees and 101.0 degrees Surface Finish: 63.0 microinches grip Material: Titanium alloy uns r54520 **Material Specification:** Nas 621, 6al-4v assn standard single material response **Thread Series Designator:** Unf **Specification Data:** 80205-nas663 professional/industrial association standard Shelf Life: N/a

Unit Of Measure:

NSN 5305-00-941-3612

Close Tolerance Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0