## NSN 5305-00-941-6423

Hexagon Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-941-6423 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.750 inches and 0.938 inches **Fastener Length:** Between 1.960 inches and 2.000 inches **Head Style:** Hexagon **Head Height:** Between 0.150 inches and 0.163 inches Width Between Flats: Between 0.428 inches and 0.438 inches **Hole Diameter:** 0.062 inches **Thread Diameter:** 0.250 inches **Hole Quantity: Hole Type:** Drilled Thready Qty Per Inch (tpi): Min. Tensile Strength (psi): 120000 pounds per square inch Hardness Rating: 23.0 rockwell c and 32.0 rockwell c Minimum Yield Strength: 85000 pounds per square inch **Hole Configuration Style:** Hexagon flats Material: Steel **Material Specification:** Sae gr 5 assn standard single material response **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Qq-p-416 type 2 cl 2 federal specification single treatment response **Thread Series Designator:** 

Unc

## NSN 5305-00-941-6423

Hexagon Head Cap Screw - Page 2 of 2



_				-		
C	h	Δ	Iŧ.		ife:	

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A003b0