NSN 5305-00-942-2166

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-942-2166

| Thread Class: |
|---|
| 2a |
| Thread Direction: |
| Right-hand |
| Thread Length: |
| 1.750 inches |
| Fastener Length: |
| 1.750 inches |
| Head Style: |
| Fillister |
| Head Diameter: |
| Between 0.250 inches and 0.270 inches |
| Head Height: |
| Between 0.106 inches and 0.113 inches |
| Hole Diameter: |
| 0.047 inches |
| Internal Drive Style: |
| Slot |
| Thread Diameter: |
| 0.164 inches |
| Hole Quantity: |
| 1 |
| Thready Qty Per Inch (tpi): |
| 32 |
| Min. Tensile Strength (psi): |
| 80000 pounds per square inch |
| Screw Material: |
| Stainless steel |
| Screw Material Specification: |
| 66 federal standard single material response |
| Screw Surface Treatment: |
| Passivate |
| Screw Surface Treatment Specification: |
| Qq-p-35 federal specification single treatment response |
| Head Hole Configuration Style: |
| Round |
| Thread Series Designator: |
| Unc |
| Shelf Life: |
| N/a |
| Unit Of Measure: |

--

NSN 5305-00-942-2166

Machine Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A500d0