NSN 5305-00-942-2214

Shoulder Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-942-2214

view Online at https://aerobasegroup.com/nsn/5305-00-942-2214
Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.355 inches and 0.375 inches
Fastener Length:
Between 1.610 inches and 1.620 inches
Head Style:
Flat chamfer
Head Diameter:
Between 0.357 inches and 0.375 inches
Head Height:
Between 0.177 inches and 0.187 inches
Shoulder Diameter:
0.246 inches first shoulder and 0.248 inches first shoulder
Shoulder Length:
1.245 inches first shoulder and 1.255 inches first shoulder
Internal Drive Style:
Hexagon
Thread Diameter:
0.190 inches
Width Across Flats:
0.125 inches
Thready Qty Per Inch (tpi):
24
Min. Tensile Strength (psi):
140000 pounds per square inch
Hardness Rating:
32.0 rockwell c and 43.0 rockwell c
Shoulder Shape:
Round first shoulder
Material:
Steel comp 4037 or steel comp 4137 or steel comp 4140 or steel comp 8630 or steel comp 8740
Surface Treatment:
Cadmium and chromate
Surface Treatment Specification:
Qq-p-416 type 2 cl 3 federal specification single treatment response
Thread Series Designator:
Unc
Shelf Life:
N/a

NSN 5305-00-942-2214

Shoulder Screw - Page 2 of 2



			ure:	

--

Demilitarization:

No

Fiig:

A003b0