Socket Head Cap Screw - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5305-00-942-2216



Thread Class: 3a **Thread Direction: Right-hand Thread Length:** Between 1.250 inches and 1.375 inches Fastener Length: 1.750 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.550 inches and 0.562 inches **Head Height:** Between 0.368 inches and 0.375 inches Hole Diameter: 0.064 inches **Internal Drive Style:** Hexagon **Thread Diameter:** 0.312 inches Width Across Flats: Between 0.312 inches and 0.316 inches Hole Quantity: 6 Hole Type: Drilled Thready Qty Per Inch (tpi): 18 Min. Tensile Strength (psi): 80000 pounds per square inch Hardness Rating: 80.0 rockwell b **Minimum Yield Strength:** 30000 pounds per square inch Hole Configuration Style: Round internal hexagon Material: Steel comp 302 or steel comp 303 or steel comp 304 or steel comp 305 or steel comp 316 **Material Specification:** 66 federal standard all material responses **Surface Treatment:** Passivate

NSN 5305-00-942-2216

Socket Head Cap Screw - Page 2 of 2



Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0