

View Online at <https://aerobasegroup.com/nsn/5305-00-942-8495>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.067 inches and 0.125 inches

Fastener Length:

Between 0.095 inches and 0.125 inches

Head Style:

Flat chamfer

Head Diameter:

Between 0.112 inches and 0.118 inches

Head Height:

Between 0.070 inches and 0.073 inches

Locking Feature:

Strip threads

Internal Drive Style:

Hexagon

Thread Diameter:

0.073 inches

Width Across Flats:

Between 0.063 inches and 0.064 inches

Thready Qty Per Inch (tpi):

72

Min. Tensile Strength (psi):

80000 pounds per square inch

Hardness Rating:

80.0 rockwell b

Minimum Yield Strength:

30000 pounds per square inch

Material:

Steel comp 302 fastener or steel comp 304 fastener or steel comp 305 fastener or steel comp 316 fastener or steel comp 384 fastener or steel comp xm-7 fastener

Material Specification:

Astm a493 assn standard all material responses fastener

Surface Treatment:

Passivate fastener

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response fastener

Thread Series Designator:

Unrf

Specification Data:

80205-nas1351 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0