## NSN 5305-00-943-2063

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-943-2063 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.777 inches and 0.807 inches **Fastener Length:** Between 0.860 inches and 0.890 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.457 inches and 0.468 inches **Head Height:** Between 0.306 inches and 0.312 inches **Locking Feature:** Strip threads **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.312 inches Width Across Flats: Between 0.250 inches and 0.253 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: 36.0 rockwell c and 43.0 rockwell c Minimum Yield Strength: 130000 pounds per square inch Material: Steel **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Qq-p-416 type 2 cl 3 federal specification single treatment response **Thread Series Designator:** Unf Shelf Life: N/a

--

**Unit Of Measure:** 

## NSN 5305-00-943-2063

Socket Head Cap Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0