NSN 5305-00-944-0150

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-944-0150

| Thread Class: |
|-----------------------------------------------------------------------------------------------------------------|
| 3a |
| Thread Direction: |
| Right-hand |
| Thread Length: |
| 0.342 inches |
| Fastener Length: |
| 0.547 inches |
| Head Style: |
| Fillister |
| Head Diameter: |
| Between 0.165 inches and 0.180 inches |
| Head Height: |
| Between 0.292 inches and 0.303 inches |
| Hole Diameter: |
| 0.046 inches |
| Internal Drive Style: |
| Cross recess type 1 |
| Thread Diameter: |
| 0.190 inches |
| Hole Quantity: |
| 1 |
| Thready Qty Per Inch (tpi): |
| 24 |
| Min. Tensile Strength (psi): |
| 125000 pounds per square inch |
| Screw Material: |
| Steel comp 8630 |
| Screw Material Specification: |
| Mil-s-6050 military specification single material response or an-s-9 military standard single material response |
| Screw Surface Treatment Specification: |
| Qq-p-416, type 1, cl 3 federal specification single treatment response |
| Head Hole Configuration Style: |
| Round |
| Thread Series Designator: |
| Unc |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |

NSN 5305-00-944-0150

Machine Screw - Page 2 of 2



Fiig:

A500d0

Mil-std (military Standard):

Mil-s-6050 spec.