Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-944-1439

T 1	
	d Class:
2a	
	d Direction:
Right-h	
	d Length:
0.380 i	
	ner Length:
0.926 i	
Head S	
Fillister	ſ
Head [Diameter:
Betwee	en 0.250 inches and 0.270 inches
Head H	leight:
Betwee	en 0.106 inches and 0.113 inches
First D	liameter From Head:
0.123 i	nches
Distan	ce From Largest Bearing Surface Of Head To End Of First Diameter:
0.500 i	nches
Interna	al Drive Style:
Slot	
Thread	d Diameter:
0.164 i	nches
Thread	dy Qty Per Inch (tpi):
32	
Extern	ally Relieved Body Diameter Quantity:
1	
Specia	al Features:
W/nons	standard point 0.047 lg 120.0 deg
Materia	al:
Steel c	omp 303 or steel comp 303se
Materia	al Specification:
Astm a	582 cond a assn standard all material responses
Surfac	e Treatment:
Passiva	ate
Thread	d Series Designator:
Unc	
Shelf L	_ife:
N/a	
Unit O	f Measure:
Demili	tarization:
No	
-	

NSN 5305-00-944-1439

Externally Relieved Body Screw - Page 2 of 2

Fiig: A003b0

