NSN 5305-00-944-4270

Shoulder Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-944-4270

Thread Class:
2a
Thread Direction:
Right-hand
Thread Length:
Between 0.214 inches and 0.258 inches
Fastener Length:
Between 0.710 inches and 0.730 inches
Head Style:
Flat chamfer
Head Diameter:
Between 0.360 inches and 0.380 inches
Head Height:
Between 0.139 inches and 0.145 inches
Shoulder Diameter:
0.249 inches first shoulder and 0.250 inches first shoulder
Shoulder Length:
0.362 inches first shoulder and 0.386 inches first shoulder
Hole Diameter:
0.038 inches
Internal Drive Style:
Slot
Thread Diameter:
0.190 inches
Thready Qty Per Inch (tpi):
24
Hardness Rating:
42.0 rockwell c and 50.0 rockwell c
Hole Configuration Style:
Round longitudinal hole
Shoulder Shape:
Round first shoulder
Special Features:
Undercut 0.220 in. Dia, 0.040 in. Lg
Material:
Steel
Material Specification:
Ams 5616 assn standard single material response
Thread Series Designator:
Unc
Shelf Life:
N/a

NSN 5305-00-944-4270

Shoulder Screw - Page 2 of 2



	1	:.	~	84				
ι	JN	IT	UΤ	IVI	ea	Sι	ire:	•

--

Demilitarization:

No

Fiig:

A003b0