Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-944-5870

| Thread Class: |
|--|
| |
| 2a Thread Direction: |
| |
| Right-hand |
| Thread Length: |
| 0.375 inches |
| Fastener Length: |
| 1.000 inches |
| Head Style: |
| Fillister |
| Head Diameter: |
| Between 0.389 inches and 0.414 inches |
| Head Height: |
| Between 0.161 inches and 0.170 inches |
| Hole Diameter: |
| 0.062 inches |
| First Diameter From Head: |
| 0.175 inches |
| Distance From Largest Bearing Surface Of Head To End Of First Diameter: |
| 0.625 inches |
| Internal Drive Style: |
| Slot |
| Thread Diameter: |
| 0.250 inches |
| Hole Quantity: |
| 1 |
| Ноје Туре: |
| Drilled |
| Thready Qty Per Inch (tpi): |
| 20 |
| Hole Configuration Style: |
| Round |
| Externally Relieved Body Diameter Quantity: |
| 1 |
| Material: |
| Steel comp 302 or steel comp 303 or steel comp 304 or steel comp 305 or steel comp 316 |
| Material Specification: |
| Aisi assn standard all material responses or sae assn standard all material responses |
| Surface Treatment: |
| Passivate |
| Thread Series Designator: |
| Unc |

NSN 5305-00-944-5870

Externally Relieved Body Screw - Page 2 of 2



Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A003b0