NSN 5305-00-944-5870

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-944-5870 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.375 inches **Fastener Length:** 1.000 inches **Head Style:** Fillister **Head Diameter:** Between 0.389 inches and 0.414 inches **Head Height:** Between 0.161 inches and 0.170 inches **Hole Diameter:** 0.062 inches First Diameter From Head: 0.175 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.625 inches **Internal Drive Style:** Slot **Thread Diameter:** 0.250 inches **Hole Quantity: Hole Type:** Drilled Thready Qty Per Inch (tpi): 20 **Hole Configuration Style: Externally Relieved Body Diameter Quantity:** Material: Steel comp 302 or steel comp 303 or steel comp 304 or steel comp 305 or steel comp 316 **Material Specification:** Aisi assn standard all material responses or sae assn standard all material responses **Surface Treatment: Passivate Thread Series Designator:**

Unc

NSN 5305-00-944-5870

Externally Relieved Body Screw - Page 2 of 2



SI	hel	f L	ife	:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0