## NSN 5305-00-944-5929

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-944-5929

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.394 inches and 0.438 inches
Fastener Length:
Between 0.456 inches and 0.500 inches
Head Style:
Pan
Head Diameter:
Between 0.357 inches and 0.373 inches
Head Height:
Between 0.122 inches and 0.133 inches
Internal Drive Style:
Cross recess type 1
Thread Diameter:
0.190 inches
Thready Qty Per Inch (tpi):
32
Min. Tensile Strength (psi):
125000 pounds per square inch
Hardness Rating:
26.0 rockwell c
Screw Material:
Steel comp 4037 or steel comp 8630
Screw Material Specification:
Mil-s-8695 military specification 1st material response or mil-s-6050 military specification 2nd material response
Screw Surface Treatment:
Cadmium and chromate
Screw Surface Treatment Specification:
Qq-p-416 type 2 cl 3 federal specification single treatment response
Thread Series Designator:
Unf
Shelf Life:
N/a
Unit Of Measure:
<del>-</del>
Demilitarization:
No
Fiig:
A500d0

## NSN 5305-00-944-5929

Machine Screw - Page 2 of 2



Mil-std (military Standard):

Mil-s-8695 spec.