NSN 5305-00-944-7553

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-944-7553 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.350 inches and 0.400 inches **Fastener Length:** Between 1.048 inches and 1.078 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.578 inches and 0.633 inches **Grip Diameter:** Between 0.3110 inches and 0.3120 inches **Internal Drive Style:** High-torque **Thread Diameter:** 0.312 inches **Grip Length:** Between 0.678 inches and 0.698 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 160000 pounds per square inch **Countersink Angle:** Between 99.0 degrees and 101.0 degrees Surface Finish: 32.0 microinches threads Material: Steel comp 4130 **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Qq-p-416 type 2 cl 2 federal specification single treatment response **Thread Series Designator:** Unjf **Specification Data:** 80205-nas1505 professional/industrial association standard Shelf Life: N/a

Unit Of Measure:

NSN 5305-00-944-7553

Close Tolerance Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0