NSN 5305-00-944-7555

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-944-7555

view Online at https://aerobasegroup.com/hsh/3300-00-344-7333
Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.350 inches and 0.400 inches
Fastener Length:
Between 1.672 inches and 1.702 inches
Head Style:
Flat countersunk
Head Diameter:
Between 0.578 inches and 0.634 inches
Grip Diameter:
Between 0.3110 inches and 0.3120 inches
Internal Drive Style:
High-torque
Thread Diameter:
0.312 inches
Grip Length:
Between 1.302 inches and 1.322 inches
Thready Qty Per Inch (tpi):
24
Min. Tensile Strength (psi):
160000 pounds per square inch
Hardness Rating:
36.0 rockwell c and 40.0 rockwell c
Countersink Angle:
Between 99.0 degrees and 101.0 degrees
Surface Finish:
32.0 microinches top of head
Product Name:
Navy special project
Material:
Steel comp 4140 or steel comp 8740 or steel comp e4340 or steel comp 4340 or steel comp 8735 or steel comp 4130 or steel comp
6150
Surface Treatment:
Cadmium and chromate
Surface Treatment Specification:
Qq-p-416 type 2 cl 2 federal specification single treatment response
Thread Series Designator:
Lloif

Specification Data:

80205-nas1505 professional/industrial association standard

NSN 5305-00-944-7555

Close Tolerance Screw - Page 2 of 2



_				-		
C	h	Δ	Iŧ.		ife:	

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0