## NSN 5305-00-945-2536

Shoulder Screw - Page 1 of 2

3a

24

Unf

N/a

---

View Online at https://aerobasegroup.com/nsn/5305-00-945-2536



## **Thread Class: Thread Direction: Right-hand Thread Length:** Between 0.282 inches and 0.432 inches Fastener Length: Between 1.875 inches and 1.922 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.756 inches and 0.760 inches Shoulder Diameter: 0.389 inches first shoulder and 0.390 inches first shoulder Shoulder Length: 1.344 inches first shoulder and 1.366 inches first shoulder **Internal Drive Style:** High-torque **Thread Diameter:** 0.375 inches Thready Qty Per Inch (tpi): Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: 36.0 rockwell c and 40.0 rockwell c **Countersink Angle:** 100.0 degrees Shoulder Shape: Round first shoulder Material: Steel comp e4340 or steel comp 4340 or steel comp 8740 or steel comp 8735 or steel comp 6150 or steel comp 4140 or steel comp 4037 or steel comp 4130 Surface Treatment: Cadmium and chromate **Surface Treatment Specification:** Qq-p-416 type 2 cl 3 federal specification single treatment response **Thread Series Designator:** Shelf Life: Unit Of Measure:

## NSN 5305-00-945-2536

Shoulder Screw - Page 2 of 2

Demilitarization:

No

Fiig:

A003b0

