NSN 5305-00-945-4652

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-945-4652 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.175 inches and 0.195 inches **Fastener Length:** Between 0.310 inches and 0.330 inches **Head Style:** Hexagon **Head Height:** Between 0.050 inches and 0.070 inches Width Between Flats: 0.218 inches **First Diameter From Head:** Between 0.123 inches and 0.128 inches **Second Diameter From Head:** Between 0.075 inches and 0.080 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.080 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: 0.135 inches **Internal Drive Style:** W/o internal drive **Thread Diameter:** 0.112 inches Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity:** 2 Material: Steel comp 1212 **Material Specification:** Qq-s-637, condition f federal specification single material response **Surface Treatment:** Cadmium **Surface Treatment Specification:** Qq-p-416, type 2, class 3 federal specification single treatment response **Thread Series Designator:** Unc Shelf Life: N/a

NSN 5305-00-945-4652

Externally Relieved Body Screw - Page 2 of 2



ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

No

Fiig:

A003b0