

View Online at <https://aerobasegroup.com/nsn/5305-00-945-6337>

Thread Class:

2a

Thread Direction:

Right-hand

Thread Length:

0.281 inches

Fastener Length:

0.750 inches

Head Style:

Pan no. 2

Head Diameter:

Between 0.473 inches and 0.492 inches

Head Height:

Between 0.130 inches and 0.144 inches

First Diameter From Head:

Between 0.160 inches and 0.180 inches

Distance From Largest Bearing Surface Of Head To End Of First Diameter:

0.469 inches

Internal Drive Style:

Slot

Thread Diameter:

0.250 inches

Thready Qty Per Inch (tpi):

28

Externally Relieved Body Diameter Quantity:

1

Product Name:

Navy special project

Special Features:

Material document and classification reply 23 qq-s-763, reply 24 qq-s-763, reply 25 qq-s-763, reply 26 qq-s-763, reply 27 qq-s-763, reply 28 qq-s-763, reply 29 qq-s-763, reply 30 qq-s-763, reply 31 qq-s-763, reply 32 astm a582, reply 33 astm a582, reply 34 qq-s-763, reply 35 astm a582

Material:

Steel comp 202 or steel comp 302 or steel comp 303se or steel comp 304 or steel comp 304l or steel comp 305 or steel comp 309 or steel comp 310 or steel comp 316 or steel comp 316l or steel comp 317 or steel comp 321 or steel comp 322 or steel comp 324 or steel comp 347 or steel comp 403 or steel comp 410 or steel comp 414 or steel comp 416se or steel comp 420 or steel comp 429 or steel comp 1010 or steel comp 430fse or steel comp 440a or steel comp 440b or steel comp 440c or steel comp 440f or steel comp 446 or steel comp 303 or steel comp 416 or steel comp 430 or steel comp 431

Material Specification:

Qq-s-763 federal specification all material responses

Surface Treatment:

Passivate

Thread Series Designator:

Unf

Shelf Life:

Demilitarization:

No

Fig:

A003b0