NSN 5305-00-945-8589

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-945-8589 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.316 inches **Fastener Length:** Between 1.301 inches and 1.348 inches **Head Style:** Round **Head Diameter:** Between 0.464 inches and 0.488 inches **Head Height:** Between 0.133 inches and 0.150 inches **Grip Diameter:** Between 0.2485 inches and 0.2495 inches **Internal Drive Style:** Offset cruciform (torque set) **Thread Diameter:** 0.250 inches **Grip Length:** Between 0.985 inches and 1.015 inches Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 180000 pounds per square inch **Surface Finish:** 32.0 microinches grip Material: Steel **Material Specification:** Mil-s-5000 military specification single material response or mil-s-6049 military specification single material response or mil-s-5626 military specification single material response **Surface Treatment:** Cadmium **Surface Treatment Specification:** Qq-p-416 type 2 cl 3 federal specification single treatment response **Thread Series Designator:** Unf

N/a

Shelf Life:

Unit Of Measure:

NSN 5305-00-945-8589

Close Tolerance Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5000 spec.