## NSN 5305-00-945-8596

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-945-8596

3aThread Direction:Right-handThread Length:0.250 inchesFastener Length:Between 0.234 inches and 0.266 inchesHead Style:Flat chamferHead Diameter:Between 0.218 inches and 0.226 inchesHead Height:Between 0.122 inches and 0.226 inchesHole Diameter:Between 0.122 inches and 0.126 inchesHornal Drive Style:HexagonThread Diameter:0.112 inchesWidth Across Flats:Between 0.1094 inches and 0.1111 inchesHole Quantity:6
Right-handRight-handThread Length:0.250 inchesFastener Length:Between 0.234 inches and 0.266 inchesHead Style:Flat chamferHead Diameter:Between 0.218 inches and 0.226 inchesHead Height:Between 0.122 inches and 0.126 inchesHole Diameter:Between 0.026 inches and 0.126 inchesHoread Height:Between 0.122 inches and 0.126 inchesHoread Diameter:Between 0.026 inches and 0.031 inchesInternal Drive Style:HexagonThread Diameter:0.112 inchesWidth Across Flats:Between 0.1094 inches and 0.1111 inchesHole Quantity:6
Thread Length:0.250 inchesFastener Length:Between 0.234 inches and 0.266 inchesHead Style:Flat chamferHead Diameter:Between 0.218 inches and 0.226 inchesHead Height:Between 0.122 inches and 0.126 inchesHole Diameter:Between 0.026 inches and 0.031 inchesInternal Drive Style:HexagonThread Diameter:0.112 inchesWidth Across Flats:Between 0.1094 inches and 0.1111 inchesHole Quantity:6
0.250 inches Fastener Length: Between 0.234 inches and 0.266 inches Head Style: Flat chamfer Head Diameter: Between 0.218 inches and 0.226 inches Head Height: Between 0.122 inches and 0.126 inches Hole Diameter: Between 0.026 inches and 0.031 inches Internal Drive Style: Hexagon Thread Diameter: 0.112 inches Width Across Flats: Between 0.1094 inches and 0.1111 inches Hole Quantity: 6
Fastener Length:Between 0.234 inches and 0.266 inchesHead Style:Flat chamferHead Diameter:Between 0.218 inches and 0.226 inchesHead Height:Between 0.122 inches and 0.126 inchesHole Diameter:Between 0.026 inches and 0.031 inchesInternal Drive Style:HexagonThread Diameter:0.112 inchesWidth Across Flats:Between 0.1094 inches and 0.1111 inchesHole Quantity:6
Between 0.234 inches and 0.266 inches Head Style: Flat chamfer Head Diameter: Between 0.218 inches and 0.226 inches Head Height: Between 0.122 inches and 0.126 inches Hole Diameter: Between 0.026 inches and 0.031 inches Internal Drive Style: Hexagon Thread Diameter: 0.112 inches Width Across Flats: Between 0.1094 inches and 0.1111 inches Hole Quantity: 6
Head Style:Flat chamferHead Diameter:Between 0.218 inches and 0.226 inchesHead Height:Between 0.122 inches and 0.126 inchesHole Diameter:Between 0.026 inches and 0.031 inchesInternal Drive Style:HexagonThread Diameter:0.112 inchesWidth Across Flats:Between 0.1094 inches and 0.1111 inchesHole Quantity:6
Flat chamfer Head Diameter: Between 0.218 inches and 0.226 inches Head Height: Between 0.122 inches and 0.126 inches Hole Diameter: Between 0.026 inches and 0.031 inches Internal Drive Style: Hexagon Thread Diameter: 0.112 inches Width Across Flats: Between 0.1094 inches and 0.1111 inches Hole Quantity: 6
Head Diameter:Between 0.218 inches and 0.226 inchesHead Height:Between 0.122 inches and 0.126 inchesHole Diameter:Between 0.026 inches and 0.031 inchesInternal Drive Style:HexagonThread Diameter:0.112 inchesWidth Across Flats:Between 0.1094 inches and 0.1111 inchesHole Quantity:6
Between 0.218 inches and 0.226 inches Head Height: Between 0.122 inches and 0.126 inches Hole Diameter: Between 0.026 inches and 0.031 inches Internal Drive Style: Hexagon Thread Diameter: 0.112 inches Width Across Flats: Between 0.1094 inches and 0.1111 inches Hole Quantity: 6
Head Height:Between 0.122 inches and 0.126 inchesHole Diameter:Between 0.026 inches and 0.031 inchesInternal Drive Style:HexagonThread Diameter:0.112 inchesWidth Across Flats:Between 0.1094 inches and 0.1111 inchesHole Quantity:6
Between 0.122 inches and 0.126 inches Hole Diameter: Between 0.026 inches and 0.031 inches Internal Drive Style: Hexagon Thread Diameter: 0.112 inches Width Across Flats: Between 0.1094 inches and 0.1111 inches Hole Quantity: 6
Hole Diameter: Between 0.026 inches and 0.031 inches Internal Drive Style: Hexagon Thread Diameter: 0.112 inches Width Across Flats: Between 0.1094 inches and 0.1111 inches Hole Quantity: 6
Between 0.026 inches and 0.031 inches Internal Drive Style: Hexagon Thread Diameter: 0.112 inches Width Across Flats: Between 0.1094 inches and 0.1111 inches Hole Quantity: 6
Internal Drive Style: Hexagon Thread Diameter: 0.112 inches Width Across Flats: Between 0.1094 inches and 0.1111 inches Hole Quantity: 6
Hexagon Thread Diameter: 0.112 inches Width Across Flats: Between 0.1094 inches and 0.1111 inches Hole Quantity: 6
Thread Diameter: 0.112 inches Width Across Flats: Between 0.1094 inches and 0.1111 inches Hole Quantity: 6
0.112 inches Width Across Flats: Between 0.1094 inches and 0.1111 inches Hole Quantity: 6
Width Across Flats: Between 0.1094 inches and 0.1111 inches Hole Quantity: 6
Between 0.1094 inches and 0.1111 inches Hole Quantity: 6
Hole Quantity: 6
6
Hole Type:
Drilled
Thready Qty Per Inch (tpi):
40
Hardness Rating:
32.0 rockwell c and 38.0 rockwell c
Hole Configuration Style:
Round internal hexagon
Surface Finish:
32.0 microinches threads
Material:
Stainless steel
Material Specification:
Ams 5616 assn standard single material response
Thread Series Designator:
Unf
Shelf Life:
N/a

## NSN 5305-00-945-8596

Socket Head Cap Screw - Page 2 of 2

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A003b0

