Externally Relieved Body Screw - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5305-00-947-6691

Thread Class: 2a Thread Direction: Right-hand Thread Length: 0.250 inches Fastener Length: 1.000 inches Fastener Length: 1.000 inches Head Style: Head Style: Head Style: Head Height: 0.205 inches Width Between Flats: 0.205 inches First Diameter From Head: 0.435 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.750 inches Internal Drive Style: Stot Thread Diameter: 0.250 inches Thread Quy Per Inch (tpi): 20
Thread Direction:Right-handThread Length:0.250 inchesFastener Length:1.000 inchesHead Style:Head Style:Head Style:0.250 inchesBeader Length:0.205 inchesWidth Between Flats:0.205 inchesFirst Diameter From Head:0.185 inchesDistance From Largest Bearing Surface Of Head To End Of First Diameter:0.750 inchesStotThread Diameter:0.250 inchesStotThread Diameter:0.250 inchesStotStotThread Diameter:0.250 inchesStot
Right-handThread Length:0.250 inchesFastener Length:1.000 inchesHead Style:Head Style:Head Style:Head Height:0.205 inchesWith Between Flats:0.205 inchesFirst Diameter From Head:0.185 inchesDistance From Largest Bearing Surface Of Head To End Of First Diameter:0.750 inchesInternal Drive Style:StotClassDistance From Largest Bearing Surface Of Head To End Of First Diameter:0.750 inchesInternal Drive Style:StotThread Diameter:0.250 inchesThread Diameter:0.250 inchesStotThread Diameter:0.250 inchesThread Diameter: <t< td=""></t<>
Thread Length:         0.250 inches         Fastener Length:         1.000 inches         Head Style:         Head Style:         Head Reight:         0.205 inches         Head Height:         0.205 inches         Width Between Flats:         0.435 inches         First Diameter From Head:         0.185 inches         Distance From Largest Bearing Surface Of Head To End Of First Diameter:         0.750 inches         Internal Drive Style:         Stot         Thread Diameter:         0.250 inches
0.250 inches Fastener Length: 1.000 inches Head Style: Head Style: Hexagon Head Height: 0.205 inches Vidth Between Flats: 0.435 inches First Diameter From Head: 0.435 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.750 inches Internal Drive Style: Slot Thread Diameter: 0.250 inches Thread Diameter: 0.250 inches
Fastener Length:1.000 inchesHead Style:Head Style:HexagonHead Height:0.205 inchesWidth Between Flats:0.435 inchesFirst Diameter From Head:0.185 inchesDistance From Largest Bearing Surface Of Head To End Of First Diameter:0.750 inchesInternal Drive Style:SlotChread Diameter:0.250 inchesThread Diameter:0.250 inches20
1.000 inches Head Style: Hexagon Head Height: 0.205 inches O.205 inches Width Between Flats: 0.205 inches First Diameter From Head: 0.435 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.750 inches Internal Drive Style: Slot Thread Diameter: 0.250 inches Distance From Largest Delated To End Of First Diameter: 0.250 inches Thread Diameter: 0.250 inches
Head Style:HexagonHead Height:0.205 inchesWidth Between Flats:0.435 inchesFirst Diameter From Head:0.185 inchesDistance From Largest Bearing Surface Of Head To End Of First Diameter:0.750 inchesInternal Drive Style:SlotThread Diameter:0.250 inchesThread Diameter:0.250 inches20
HexagonHead Height:0.205 inchesWidth Between Flats:0.435 inchesFirst Diameter From Head:0.185 inchesDistance From Largest Bearing Surface Of Head To End Of First Diameter:0.750 inchesInternal Drive Style:StotThread Diameter:0.250 inches1.250 inches2.50 inches2.50 inches2.50 inches3.50 inches<
Head Height:0.205 inchesWidth Between Flats:0.435 inchesFirst Diameter From Head:0.185 inchesDistance From Largest Bearing Surface Of Head To End Of First Diameter:0.750 inchesInternal Drive Style:SlotThread Diameter:0.250 inches20
0.205 inches Width Between Flats: 0.435 inches First Diameter From Head: 0.185 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.750 inches Internal Drive Style: Slot Thread Diameter: 0.250 inches 20
Width Between Flats:0.435 inchesFirst Diameter From Head:0.185 inchesDistance From Largest Bearing Surface Of Head To End Of First Diameter:0.750 inchesInternal Drive Style:SlotThread Diameter:0.250 inchesThread Diameter:0.250 inches20
0.435 inches First Diameter From Head: 0.185 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.750 inches Internal Drive Style: Slot Thread Diameter: 0.250 inches Thready Qty Per Inch (tpi): 20
First Diameter From Head:0.185 inchesDistance From Largest Bearing Surface Of Head To End Of First Diameter:0.750 inchesInternal Drive Style:SlotThread Diameter:0.250 inchesThready Qty Per Inch (tpi):20
0.185 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.750 inches Internal Drive Style: Slot Thread Diameter: 0.250 inches Thready Qty Per Inch (tpi): 20
Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.750 inches Internal Drive Style: Slot Thread Diameter: 0.250 inches Thready Qty Per Inch (tpi): 20
0.750 inches Internal Drive Style: Slot Thread Diameter: 0.250 inches Thready Qty Per Inch (tpi): 20
Internal Drive Style: Slot Thread Diameter: 0.250 inches Thready Qty Per Inch (tpi): 20
Slot Thread Diameter: 0.250 inches Thready Qty Per Inch (tpi): 20
Thread Diameter: 0.250 inches Thready Qty Per Inch (tpi): 20
0.250 inches Thready Qty Per Inch (tpi): 20
Thready Qty Per Inch (tpi): 20
20
1
Material:
Stainless steel
Surface Treatment:
Passivate
Thread Series Designator:
Unc
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A003b0