NSN 5305-00-947-7034

Hexagon Head Cap Screw - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5305-00-947-7034



Thread Class: 2a **Thread Direction:** Right-hand Thread Length: Between 1.500 inches and 1.719 inches **Fastener Length:** Between 2.650 inches and 2.750 inches **Head Style:** Hexagon **Head Height:** Between 0.378 inches and 0.403 inches Width Between Flats: Between 0.922 inches and 0.937 inches **Hole Diameter:** 0.094 inches **Thread Diameter:** 0.625 inches **Hole Quantity: Hole Type:** Drilled Thready Qty Per Inch (tpi): Min. Tensile Strength (psi): 150000 pounds per square inch Hardness Rating: 32.0 rockwell c and 38.0 rockwell c Minimum Yield Strength: 120000 pounds per square inch **Hole Configuration Style:** Hexagon flats Material: Steel **Material Specification:** Sae gr 8 assn standard single material response **Surface Treatment:** Zinc and chromate **Surface Treatment Specification:** Astm b633 type 2 sc 3 assn standard single treatment response **Thread Series Designator:** Unc

NSN 5305-00-947-7034

Hexagon Head Cap Screw - Page 2 of 2



_				
c	hο	JIF.		ife:
J			_	HG.

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0