

View Online at <https://aerobasegroup.com/nsn/5305-00-948-0673>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 1.750 inches and 2.000 inches

**Fastener Length:**

Between 3.906 inches and 4.000 inches

**Head Style:**

Hexagon

**Head Height:**

Between 0.455 inches and 0.483 inches

**Width Between Flats:**

Between 1.100 inches and 1.125 inches

**Thread Diameter:**

0.750 inches

**Thready Qty Per Inch (tpi):**

10

**Min. Tensile Strength (psi):**

70000 pounds per square inch

**Minimum Yield Strength:**

30000 pounds per square inch

**Surface Finish:**

63.0 microinches threads

**Material:**

Steel comp 301 or steel comp 302 or steel comp 302b or steel comp 303 or steel comp 303se or steel comp 304 or steel comp 304l or steel comp 305 or steel comp 308 or steel comp 309 or steel comp 309s or steel comp 310 or steel comp 310s or steel comp 314 or steel comp 316 or steel comp 316l or steel comp 317 or steel comp 321 or steel comp 347 or steel comp 348 or steel comp 384 or steel comp 385

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response

**Thread Series Designator:**

Unc

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0