## NSN 5305-00-948-0768

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-948-0768

| Thread Class:   |
|---|
| 2a  |
| Thread Direction:                                     |
| Right-hand  |
| Thread Length:  |
| Between 1.027 inches and 1.125 inches                 |
| Fastener Length:                                      |
| Between 1.063 inches and 1.125 inches                 |
| Head Style:   |
| Fillister   |
| Head Diameter:  |
| Between 0.124 inches and 0.140 inches                 |
| Head Height:  |
| Between 0.053 inches and 0.062 inches                 |
| Hole Diameter:  |
| 0.031 inches  |
| Internal Drive Style:                                 |
| Slot  |
| Thread Diameter:                                      |
| 0.086 inches  |
| Hole Quantity:  |
| 1   |
| Thready Qty Per Inch (tpi):                           |
| 56  |
| Min. Tensile Strength (psi):                          |
| 60000 pounds per square inch                          |
| Screw Material:                                       |
| Steel comp 1010 or steel comp 1011 or steel comp 1013 |
| Screw Surface Treatment:                              |
| Cadmium and chromate                                  |
| Head Hole Configuration Style:                        |
| Round   |
| Thread Series Designator:                             |
| Unc   |
| Specification Or Standard:                            |
| 1 type and 5s style                                   |
| Departure From Cited Designator:                      |
| As modified by length                                 |
| Shelf Life:   |
| N/a   |
| Unit Of Measure:                                      |

--

## NSN 5305-00-948-0768

Machine Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A500d0