NSN 5305-00-948-4035

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-948-4035

Thread Class:
2a
Thread Direction:
Right-hand
Thread Length:
Between 0.839 inches and 0.875 inches
Fastener Length:
0.875 inches
Head Style:
Fillister
Head Diameter:
Between 0.124 inches and 0.140 inches
Head Height:
Between 0.055 inches and 0.062 inches
Hole Diameter:
0.031 inches
Internal Drive Style:
Slot
Thread Diameter:
0.086 inches
Hole Quantity:
1
Thready Qty Per Inch (tpi):
56
Min. Tensile Strength (psi):
80000 pounds per square inch
Screw Material:
Steel comp 302 or steel comp 303 or steel comp 304 or steel comp 305 or steel comp 316
Screw Material Specification:
66 federal standard all material responses
Screw Surface Treatment:
Passivate
Screw Surface Treatment Specification:
Qq-p-35 federal specification single treatment response
Head Hole Configuration Style:
Round
Thread Series Designator:
Unc
Shelf Life:
N/a
Unit Of Measure:

--

NSN 5305-00-948-4035

Machine Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A500d0