NSN 5305-00-948-4037

Machine Screw - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5305-00-948-4037



Thread Class:

2a

Thread Direction:

Right-hand

Thread Length:

Between 0.167 inches and 0.250 inches

Fastener Length:

Between 0.219 inches and 0.250 inches

Head Style:

Fillister

Head Diameter:

Between 0.292 inches and 0.313 inches

Head Height:

Between 0.123 inches and 0.130 inches

Hole Diameter:

0.046 inches

Internal Drive Style:

Slot

Thread Diameter:

0.190 inches

Hole Quantity:

1

Thready Qty Per Inch (tpi):

24

Min. Tensile Strength (psi):

80000 pounds per square inch

Screw Material:

Steel comp 302 or steel comp 303 or steel comp 304 or steel comp 305 or steel comp 316

Screw Material Specification:

66 federal standard all material responses

Screw Surface Treatment:

Passivate

Screw Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

Head Hole Configuration Style:

Hexagon flats

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

NSN 5305-00-948-4037

Machine Screw - Page 2 of 2

Demilitarization:

No

Fiig:

A500d0

