NSN 5305-00-948-4042

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-948-4042

| View Online at https://aerobasegroup.com/nsn/5305-00-948-4042 | |
|--|--|
| Thread Class: | |
| 2a | |
| Thread Direction: | |
| Right-hand | |
| Thread Length: | |
| Between 0.276 inches and 0.312 inches | |
| Fastener Length: | |
| Between 0.281 inches and 0.312 inches | |
| Head Style: | |
| Fillister | |
| Head Diameter: | |
| Between 0.124 inches and 0.140 inches | |
| Head Height: | |
| Between 0.055 inches and 0.062 inches | |
| Hole Diameter: | |
| 0.031 inches | |
| Internal Drive Style: | |
| Slot | |
| Thread Diameter: | |
| 0.086 inches | |
| Hole Quantity: | |
| 1 | |
| Thready Qty Per Inch (tpi): | |
| 56 | |
| Min. Tensile Strength (psi): | |
| 80000 pounds per square inch | |
| Screw Material: | |
| Steel comp 302 or steel comp 303 or steel comp 304 or steel comp 305 or steel comp 316 | |
| Screw Material Specification: | |
| 66 federal standard all material responses | |
| Screw Surface Treatment: | |
| Passivate | |
| Screw Surface Treatment Specification: | |
| Qq-p-35 federal specification single treatment response | |
| Head Hole Configuration Style: | |
| Round | |
| Thread Series Designator: | |
| Unc | |
| Shelf Life: | |
| N/a | |
| Unit Of Measure: | |

NSN 5305-00-948-4042

Machine Screw - Page 2 of 2

Demilitarization:

No

Fiig:

A500d0

