NSN 5305-00-949-3656

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-949-3656 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.234 inches and 0.250 inches **Fastener Length:** 0.500 inches **Head Style:** Flat chamfer **Head Diameter:** 0.375 inches **Head Height:** 0.046 inches **First Diameter From Head:** Between 0.155 inches and 0.156 inches **Second Diameter From Head:** Between 0.074 inches and 0.078 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.203 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: 0.250 inches **Internal Drive Style:** Slot **Thread Diameter:** 0.112 inches Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity:** 2 Material: Steel comp 303 **Material Specification:** Astm a582, cond a assn standard single material response **Surface Treatment: Passivate Thread Series Designator:** Unc Shelf Life: N/a

--

Unit Of Measure:

NSN 5305-00-949-3656

Externally Relieved Body Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0