NSN 5305-00-949-6137

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-949-6137

| Thread Class: |
|--|
| 2a |
| Thread Direction: |
| Right-hand |
| Thread Length: |
| Between 1.375 inches and 1.500 inches |
| Fastener Length: |
| 1.500 inches |
| Head Style: |
| Fillister |
| Head Diameter: |
| Between 0.590 inches and 0.622 inches |
| Head Height: |
| Between 0.242 inches and 0.253 inches |
| Hole Diameter: |
| 0.070 inches |
| Internal Drive Style: |
| Slot |
| Thread Diameter: |
| 0.375 inches |
| Hole Quantity: |
| 1 |
| Thready Qty Per Inch (tpi): |
| 16 |
| Min. Tensile Strength (psi): |
| 80000 pounds per square inch |
| Screw Material: |
| Steel comp 302 or steel comp 303 or steel comp 304 or steel comp 305 or steel comp 316 |
| Screw Material Specification: |
| 66 federal standard all material responses |
| Screw Surface Treatment: |
| Passivate |
| Screw Surface Treatment Specification: |
| Qq-p-35 federal specification single treatment response |
| Head Hole Configuration Style: |
| Round |
| Thread Series Designator: |
| Unc |
| Shelf Life: |
| N/a |
| Unit Of Measure: |

--

NSN 5305-00-949-6137

Machine Screw - Page 2 of 2



| _ | | | | | |
|----|-----|---------|-----|---|--|
| 11 | em) | tor | 172 | n | |
| | | | | | |

No

Fiig:

A500d0