NSN 5305-00-949-9219

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-949-9219
Thread Class:
2a
Thread Direction:
Right-hand
Thread Length:
Between 0.359 inches and 0.391 inches
Fastener Length:
Between 1.172 inches and 1.203 inches
Head Style:
Knurled no. 1
Head Diameter:
Between 0.557 inches and 0.567 inches
Head Height:
Between 0.234 inches and 0.266 inches
First Diameter From Head:
Between 0.170 inches and 0.180 inches
Distance From Largest Bearing Surface Of Head To End Of First Diameter:
Between 0.803 inches and 0.823 inches
Internal Drive Style:
Slot
Thread Diameter:
0.250 inches
Thready Qty Per Inch (tpi):
28
Externally Relieved Body Diameter Quantity:
1
Material:
Steel comp 303
Material Specification:
Astm a582 assn standard single material response
Surface Treatment:
Passivate
Surface Treatment Specification:
Mil-f-14072, finish e300 military specification single treatment response
Thread Series Designator:
Unf
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

No

NSN 5305-00-949-9219

Externally Relieved Body Screw - Page 2 of 2



Fiig:

A003b0

Mil-std (military Standard):

Mil-f-14072 spec.