NSN 5305-00-950-9717

Assembled Washer Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-950-9717 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.191 inches **Fastener Length:** 0.219 inches **Head Style:** Round **Head Diameter:** Between 0.193 inches and 0.211 inches **Head Height:** Between 0.075 inches and 0.086 inches Washer Quantity: **Internal Drive Style:** Slot **Thread Diameter:** 0.112 inches Thready Qty Per Inch (tpi): 40 Min. Tensile Strength (psi): 60000 pounds per square inch **Primary Washer Outside Diameter:** Between 0.220 inches and 0.230 inches **Primary Washer Style:** Flat external teeth **Primary Washer Material Thickness:** 0.014 inches Material: Steel comp 1010 **Material Specification:** Qq-s-634 federal specification single material response **Surface Treatment:** Cadmium **Surface Treatment Specification:** Qq-p-416 class c federal specification single treatment response **Thread Series Designator:** Unc Shelf Life:

N/a

NSN 5305-00-950-9717

Assembled Washer Screw - Page 2 of 2



	• •				
In	18	<i>(</i>)+	МЛО	201	ure:

--

Demilitarization:

No

Fiig:

A003b0